

VOCORD 24B Enclosure

Intended for the protection of cameras meant for installation in outdoor conditions. The enclosure provides year-round operation of outdoor video cameras over a wide temperature range.



Technical specifications

Network interface	
Ethernet interface	Gigabit Ethernet 1000BASE-T
Number of ports	up to 2
Power supply	
Power consumption, W	13 (2 Mp and 2,8 Mp cameras) 15 (4,1 Mp camera)
AC Power supply voltage, V	24
Operation, transportation and storage conditions	
Operational conditions	
- ingress protection	IP 67
- ambient air temperature, °C	from - 20 to + 60
- atmospheric pressure	from 84,0 to 106,7 kPa (from 630 to 800 mm Hg)
Transportation conditions	
- ambient air temperature, °C	from - 60 to + 50
- atmospheric pressure	from 12,0 kPa (90 mm Hg)
Storage conditions	
- ambient air temperature, °C	from +5 to + 40
- relative humidity	up to 80%
- atmospheric pressure	from 84,0 to 106,7 kPa (from 630 to 800 mm Hg)
Weight and dimensions parameters	
Dimensions W×D×H:	
- for housing HEG37K2A000, mm	175 × 493 × 168
- for housing HEG47K2A000, mm	175 × 590 × 168
Net weight, kg	no more than 7,0
Gross weight, kg	no more than 7,5
Reliability indicators	
Service life of product and warehouse storage life of product in manufacturers packaging, years	5

Do you want to know more?

Partnership: partnership@vocord.com
 Sales department: sales@vocord.com
 PR department: pr@vocord.com

Phone: +7 (495) 787-26-26
 Moscow, Russia
www.vocord.com